

USEFUL INFORMATION

HOW TO SELECT A TYRE

Tyre size and maximum speed of the vehicle.
The maximum load capacity per axle (Load index).
Your style driving and road condition.

MOUNTING & DISMOUNTING

Only get trained people mounting and dismounting your tyres.

TYRE PRESSURE

For safe drive, it is extremely important to drive with the right pressure.

CHECK FOLLOWING ITEMS IN REGULAR WAY

Tread Pattern


Unusual wear, tread groove separation, bulges.. etc.

Sidewall

Impact, Bulges, Ozone cracking, vehicle contact damage etc.

Pressure

The inflated pressure will be changed during long driving and changed circumstances temperature.



DISTRIBUTED BY

These data can be changed by the manufactuer without prior notice and differently applied by regions.

Printed on Jan. 2025



2025
PRODUCTS
MANUAL

POWERED BY
PERFORMANCE





**SEVEN
YEARS**
TOP QUALITY
ASSURANCE

Up to 7 Years Quality Warranty

3 Times Re-tread Guarantee



WHY ZETA

Design engineering from Europe, using the most up to date design technology available.

All types of certificates are available, like ECE, GCC, Soncap, NOM and Smartway etc.

All products have been tested and approved under EC Regulation 1229/2009, regarding Wet Grip, Rolling Resistance and External Noise which stipulated by EU.

Exclusive Distribution available to offer.

Direct factory programme, ensuring continuity of supply and competitive price.

Over 100 different sizes & applications are available, with much more to be followed in near future.

Full marketing support available.

USED AND TRUSTED BY OVER
1M USERS

TBR PRODUCT
SELECTION GUIDE



Long Haul



Steer/Trailer Position



DR909 DSR75 ZHS06 ZHS15

Drive Position



DR920 DD932 ZHD06 ZHD05 ZHD09

All -Position

Regional



ZRS67 ZRS11



DR938 ZRD16 ZRD07



DR905 DR902

Mixed Service



DR926 DR928 ZXD28 ZXD45



DR908 ZXA18 ZXA38 ZXA70

Off Road



DR930 ZMA84

Urban



DR966



LONG HAUL

DSR75	DR909	ZHS06	ZHS15	DR920
DD932	ZHD06	ZHD05	ZHD09	



DSR75



ULTRA PREMIUM FUEL EFFICIENT
STEER/TRAILER POSITION TYRE

- ◆ Four straight line designed grooves ensure excellent steering performance and longer mileage.
- ◆ Soft tread features unique steel splice, contacting earth evenly.
- ◆ Perfect handling on dry and wet surfaces thanks to refined pattern structure.
- ◆ Raised block in the bottom of tread effectively prevents pebble jammed.

DSR75

Size	PR	LI/SI	S.Rim	SW (mm)	OD (mm)	TD (mm)	T.W. (mm)	Max Load S (kg)	Max Load D (kg)	Pressure (kpa)
11R22.5	16	146/143M (148/145L)	8.25	277	1054	15	202	3000	2725	830



DR909



- ◆ Advanced tread compounds and internal construction provides low rolling resistance and greater mileage.
- ◆ Extensive tread siping helps fight irregular wear in free rolling positions.
- ◆ Features extensive siping and side-shoulder decoupling groove to enhance even wear, traction in long haul steer axle positions.

**ULTRA PREMIUM FUEL EFFICIENT
STEER/TRAILER POSITION TYRE**

DR909

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load		Pressure (kpa)
								S (kg)	D (kg)	
12R22.5	18	152/149L	9.00	300	1077	15.5	235	3550	3250	930
295/80R22.5	20	154/152M	9.00	298	1044	15.5	230	3750	3550	930
315/80R22.5	20	156/151M	9.00	312	1076	15.0	242	4000	3450	850



ZHS06



**PREMIUM LONG DISTANCE SERVICE
STEER/TRAILER POSITION TYRE**

- ◆ Wide and strong shoulder ribs increase greatly the service mileage.
- ◆ Horizontal sipes provide the lasting grip and stability.
- ◆ Brief pattern design effectively decreases the rolling resistance.

ZHS06

Size	PR	LI/SI	S.Rim	SW (mm)	OD (mm)	TD (mm)	T.W. (mm)	Max Load		Pressure (kpa)
								S (kg)	D (kg)	
11R22.5	16	146/143M	8.25	279	1054	15.0	220	3000	2725	830
11R24.5	16	149/146M	8.25	279	1092	15.0	220	3250	3000	830
295/75R22.5	16	146/143M	9.00	298	1044	15.0	228	3000	2725	830



ZHS15



- ♦ Wide and strong shoulder ribs increase greatly the service mileage.
- ♦ Horizontal sipes provide the lasting grip and stability.
- ♦ Brief pattern design effectively decreases the rolling resistance.

PREMIUM LONG DISTANCE SERVICE STEER/TRAILER POSITON TYRE

ZHS15

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load		Pressure (kpa)
								S (kg)	D (kg)	
295/80R22.5	18	154/149M	9.00	298	1044	16.5	243	3750	3250	900



DR920



ULTRA PREMIUM FUEL EFFICIENT
DRIVE POSITION TYRE

- ♦ Advanced tread compounds and internal construction provides low rolling resistance and longer mileage.
- ♦ Closed-shoulder tread design provides even wear while maintaining excellent traction.
- ♦ Deep 26/32" tread with stone drilling protectors promotes long original mileage.

DR920

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load		Pressure (kpa)
								S (kg)	D (kg)	
11R22.5	16	148/145L	8.25	279	1054	20.5	210	3150	2900	840
295/80R22.5	16	152/148M	9.00	298	1050	20.5	230	3550	3150	830
315/80R22.5	20	156/151M	9.00	312	1076	20.5	240	4000	3450	850



DD932



- ◆ Open shoulder and mixed pattern structure design provides excellent traction performance and slipper resistance.
- ◆ Shoulder reinforcement design effectively prevent the accidental damage of the tire.
- ◆ Widened the tread surface makes the tire uniform wear.

PREMIUM HIGHWAY
SERVICE DRIVE POSITION TYRE

DD932

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
245/70R19.5	16	141/140M	7.50	248	839	13.0	198	2575 2500	850



ZHDO6



PREMIUM LONG DISTANCE SERVICE
DRIVE POSITION TYRE

- ◆ Optimize the footprint for even wear and long tread longevity.
- ◆ Individual blocks design provides the excellent traction performance and grip on wet road.
- ◆ Closed shouders ensure the stability of high speed driving.

ZHDO6

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
11R22.5	16	146/143L	8.25	279	1054	20.6	220	3000 2725	830
11R24.5	16	149/146L	8.25	279	1104	21.0	220	3250 3000	830
295/75R22.5	16	146/143M	9.00	298	1050	20.6	220	3000 2725	830



ZHD05



- ◆ Optimized the footprint for even wear and long tread longevity.
- ◆ Individual blocks design provides the excellent traction performance and grip on wet road.

PREMIUM LONG DISTANCE SERVICE DRIVE
POSITON TYRE

ZHD05

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
295/80R22.5	18	152/149L	9.00	298	1050	20.5	256	3550 3250	900



ZHD09



PREMIUM LONG DISTANCE SERVICE DRIVE
POSITON TYRE

- ◆ Block pattern design, super performance, short braking distance and high safety performance.
- ◆ Open shoulder design provides excellent traction in wet and dry conditions.
- ◆ Using reinforced bead design, improve tire bearing capacity.

ZHD09

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
295/80R22.5	18	152/149M	9.00	298	1050	21.0	246	3550 3250	900



REGIONAL

- ZRS11
- ZRS67
- DR938
- ZRD16
- DR902
- DR905
- ZRDO7



ZRS11



PREMIUM REGIONAL STEER
POSITION TYRE

- ◆ Four longitudinal grooves provide good maneuverability and wetskid resistance.
- ◆ The fine kerf on the pattern effectively improves the grip performance and reduces the ercentric wear.
- ◆ Low fuel consumption, high safety.

ZRS11

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load		Pressure (kpa)
								S (kg)	D (kg)	
12R22.5	18	152/149M	9.00	303	1078	17.5	240	3550	3250	930
295/80R22.5	18	152/149M	9.00	298	1048	17.0	245	3550	3250	900



ZRS67



- ◆ Ensure .excellent water evacuation even pressure distribution and heat dissipation.
- ◆ Deliver stone-ejecting property.
- ◆ Deliver excellent driving and braking force.

PREMIUM REGIONAL STEER POSITION TYRE

ZRS67

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
275/80R22.5	18	149/146L	8.25	285	1013	15.0	228	3250 3000	830



DR938



ULTRA PREMIUM OPEN SHOULDER
REGIONAL DRIVE POSITION TYRE

- ◆ Innovative open shoulder tread design provides outstanding traction and promotes even wear.
- ◆ 26/32" original tread depth for excellent mileage in long and short haul applications.
- ◆ Heavy duty casing for stability and promotion of retreading.

DR938

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
295/80R22.5	16	152/148M	9.00	298	1050	20.5	242	3550 3150	830
315/80R22.5	20	156/151M	9.00	312	1082	22.0	254	4000 3450	850



ZRDO7



- ◆ Open shoulder design provides excellent traction in wet and dry conditions.
- ◆ Full-depth siping provides excellent performance throughout the life of the tread.
- ◆ Unique mixed pattern design reduces heat generation and ensures extended mileage.

PREMIUM ON ROAD DRIVE
SERVICE POSITION TYRE

ZRDO7

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load		Pressure (kpa)
								S (kg)	D (kg)	
11R22.5	16	146/143M	8.25	277	1068	22.0	220	3000	2725	830
11R24.5	16	149/146M	8.25	284	1109	22.0	220	3250	3000	830





ZRD16



- ◆ M+S pattern, with good grip character and traction character.
- ◆ Siping provides excellent performance throughout the life of the tread.
- ◆ Good anti-wearing formula provide long mileage.


PREMIUM REGIONAL DRIVE POSITION TYRE

ZRD16

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
12R22.5	18	152/149M	9.00	303	1085	20.5	240	3550 3250	930



DR902



PREMIUM LOW PROFILE
ALL-POSITION MULTI-USE TYRE

- ◆ Special tread compounds designed to fight irregular wear and provide long life in trailer and all-position applications.
- ◆ 5-rib design promotes premium handling and reduced noise.
- ◆ Four steel belts provide casing strength for excellent durability, toughness and retreadability.

DR902

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
9.5R17.5	18	143/141L	6.75	240	842	12.5	172	2725 2575	875
215/75R17.5	18	135/133J	6.00	211	767	12.5	170	2180 2060	830
235/75R17.5	18	143/141J	6.75	233	797	12.5	190	2725 2575	875
245/70R19.5	16	141/140M	7.50	248	839	13.0	198	2575 2500	850
265/70R19.5	16	143/141M	7.50	262	867	13.0	198	2725 2575	850
255/70R22.5	16	140/137M	7.50	255	930	13.5	192	2500 2300	830



DR905



- ◆ Tread pattern and heavy ply rating designed for multiple uses.
- ◆ 6-rib design excellent for free rolling applications.
- ◆ Durable casing provides long original tread life and promotes multiple retreads.

PREMIUM WIDE BASE/ALL-POSITION TYRE

DR905

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load		Pressure (kpa)
								S (kg)	D (kg)	
385/65R22.5	20	160K	11.75	389	1072	16.0	286	4500	—	900



MIXED SERVICE

DR908	DR926	DR928	ZXD28	ZXD45
ZXA18	ZXA38	ZXA70		



ZXD28



- ◆ High performance tread compound application improves the chip, cut and abrasion resistance.
- ◆ Stone rejection design in the groove bottom protects tread from stone puncture.
- ◆ Deep tread depth increases driving mileage and service life.

PREMIUM ON/OFF ROAD SERVICE DRIVE POSITION TYRE

ZXD28

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
9.5R17.5	18	143/141K	6.75	240	844	16.5	184	2725 2575	900
11R22.5	16	146/143L(148/145K)	8.25	279	1054	22.5	220	3000 2725	830
11R24.5	16	149/146L	8.25	279	1104	22.5	220	3250 3000	830



ZXD45



PREMIUM ON/OFF ROAD SERVICE DRIVE POSITION TYRE

- ◆ High performance tread compound application improves the chip, cut and abrasion resistance.
- ◆ Deep tread depth increases driving mileage and service life.
- ◆ Directional block design provides the powerful traction performance.

ZXD45

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
12R22.5	18	152/149L	9.00	302	1081	19.5	239	3550 3250	930
13R22.5	20	156/153K	9.75	320	1125	21.0	252	4000 3650	930
295/80R22.5	18	152/149L	9.00	298	1050	21.0	246	3550 3250	900
315/80R22.5	20	157/154M	9.00	312	1082	21.0	255	4120 3750	900



DR928



- ◆ Deep lateral shoulders enhance water and mud ejection.
- ◆ Directional tread design provides exceptional biting and handling in rough terrains.
- ◆ Angled tread blocks deliver outstanding self-cleaning and extended wear protection.

PREMIUM ON AND OFF ROAD DRIVE POSITION TYRE

DR928

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
8.25R16	18	130/126L	6.50H	235	855	15.0	178	1900 1700	870
9.5R17.5	18	143/141K	6.75	240	842	15.0	184	2725 2575	875
11R22.5	16	148/145L	8.25	279	1054	17.0	210	3150 2900	840
315/80R22.5	20	156/151L	9.00	312	1082	21.0	240	4000 3450	850
215/75R17.5	18	135/133J	6.00	211	767	15.0	170	2180 2060	830
235/75R17.5	18	143/141J	6.75	233	797	16.0	190	2725 2575	875



DR926



**PREMIUM OPEN SHOULDER
DRIVE POSITION TYRE**

- ◆ Open shoulder design provides excellent traction in wet and dry conditions.
- ◆ Full-depth siping provides excellent performance throughout the life of the tread.
- ◆ Heavy duty casing for stability and promotion of retreading.

DR926

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
12R22.5	16	152/149L	9.00	300	1096	18.0	230	3550 3250	930



DR908



- ♦ Strong all-position tread pattern designed for multiple on and off highway uses.
- ♦ Cut, chip and tear resistant tread compounds and heavy duty casing construction for excellent performance in tough applications.
- ♦ High load carrying capacity for heavy load applications.

PREMIUM ON AND OFF ROAD MIXED SERVICE ALL-POSITION TYRE

DR908

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
7.00R16	14	118/114L	5.50F	200	775	11.0	157	1320 1180	770
7.50R16	14	122/118L	6.00G	215	805	13.0	168	1500 1320	770
8.25R16	16	128/124L	6.50H	235	855	13.0	168	1800 1600	770
8.25R20	16	139/137K	6.50	235	974	15.0	178	2430 2300	930
10.00R20	18	149/146K	7.50	278	1055	16.0	210	3250 3000	930
11.00R20	18	152/149K	8.00	293	1085	17.0	223	3550 3250	930
11R22.5	16	148/145M	8.25	279	1054	15.0	210	3150 2900	840
12.00R20	18	154/151K	8.50	315	1125	17.5	238	3750 3450	830
12.00R24	20	160/157K	8.50	313	1226	16.0	238	4500 4125	900
12R22.5	18	152/149L	9.00	300	1085	17.0	232	3550 3250	930
13R22.5	18	154/151L	9.75	320	1124	17.5	246	3750 3450	830
295/80R22.5	18	152/149M	9.00	298	1044	15.0	230	3550 3250	900
315/80R22.5	20	156/151M	9.00	312	1076	15.0	240	4000 3450	850



ZXA18



PREMIUM ON/OFF ROAD SERVICE ALL POSITION TYRE

- ♦ Typical combined pattern improves the wear mileage.
- ♦ Special tread compound application provides good chop and cut resistance.
- ♦ Grooves design in the shoulder improves the heat dissipation performance.

ZXA18

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg) D (kg)	Pressure (kpa)
215/75R17.5	18	135/133J	6.00	211	765	14.0	180	2180 2060	830
235/75R17.5	18	143/141J	6.75	233	797	16.5	190	2725 2575	875
255/70R22.5	16	140/137M	7.50	255	930	17.0	196	2500 2300	830
275/70R22.5	18	148/145M	8.25	276	961	17.5	225	3150 2900	900
11R22.5	16	146/143L(148/145K)	8.25	279	1054	17.0	220	3000 2725	830
11R24.5	16	149/146L	8.25	279	1098	17.0	220	3250 3000	850
12R22.5	18	152/149L	9.00	302	1078	17.5	239	3550 3250	930
13R22.5	20	156/153L	9.75	320	1122	18.0	246	4000 3650	930
295/80R22.5	18	152/149L	9.00	303	1046	17.0	243.5	3550 3250	900
315/80R22.5	20	161/154K	9.00	312	1076	16.5	254	4650 3750	900



ZXA38

- ◆ Typical combined pattern improves the wear mileage.
- ◆ Special tread compound application provides good chop and cut resistance.
- ◆ Grooves design in the shoulder improves the heat dissipation performance.

PREMIUM ON/OFF ROAD SERVICE ALL POSITION TYRE

ZXA38

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load		Pressure (kpa)
								S (kg)	D (kg)	
385/65R22.5	20	164K	11.75	389	1074	18.0	300	5000	—	900



ZXA70

PREMIUM ON/OFF ROAD SERVICE ALL POSITION TYRE

- ◆ Typical combined pattern improves the wear mileage.
- ◆ Special tread compound application provides good chop and cut resistance.
- ◆ Deep tread depth increases driving mileage and service life.

ZXA70

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load		Pressure (kpa)
								S (kg)	D (kg)	
12R22.5	18	152/149L	9.00	302	1080	20.0	240	3550	3250	930



OFF ROAD

ZMA84

DR930

ZMA84

PREMIUM OFF ROAD SERVICE DRIVE POSITION TYRE

- ◆ Chip and cut resistant compounds offer long mileage and wear while reducing effect of cuts, snags and tears .
- ◆ Aggressive tread offers excellent traction for severe off-highway use.
- ◆ Unique mixed pattern design reduces heat generation and ensure extended mileage.

ZMA84

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load S (kg)	D (kg)	Pressure (kpa)
*11R22.5	16	146/143L	8.25	279	1054	23.0	220	3000	2725	830
*11R24.5	16	149/146L	8.25	279	1104	23.0	220	3250	3000	850

* * The product is in design."



DR930




- ◆ Chip, cut and abrasion resistant tread compounds Max.
- ◆ 32/32" tread depth promotes increased mileage and long service life.
- ◆ Aggressive tread offers excellent traction for severe off-highway use; no on-highway speed restrictions.

PREMIUM DEEP TREAD OFF ROAD SEVERE
SERVICE DRIVE POSITION TYRE

DR930

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load		Pressure (kpa)
								S (kg)	D (kg)	
7.50R16	14	122/118J	6.00G	215	815	18.0	174	1500	1320	770
10.00R20	18	149/146G	7.50	278	1065	23.5	216	3250	3000	930
11R22.5	16	148/145G	8.25	315	1136	23.0	216	3150	2900	840
12R22.5	18	152/149G	9.00	300	1096	23.0	231	3550	3250	930
13R22.5	20	154/151G (156/150F)	9.75	320	1128	23.5	252	3750	3450	830
295/80R22.5	18	152/149J	9.00	298	1050	23.0	235	3550	3250	900
315/80R22.5	20	156/151G	9.00	312	1082	23.0	246	4000	3450	850



URBAN

DR966



DR966



- ◆ Premium tread design with wide shoulders prevent from irregular wear and provide high durability.
- ◆ The thicker sidewall can prevent the damage from outside.
- ◆ Deep pattern design and special formula offers excellent wear resistance.

PREMIUM SPECIAL URBAN BUS
ALL-POSITION TYRE

DR966

Size	PR	LI/SI	S.Rim	S.W. (mm)	O.D. (mm)	T.D. (mm)	T.W. (mm)	Max Load		Pressure (kpa)
								S (kg)	D (kg)	
295/80R22.5	18	152/149M	9.00	298	1050	19.0	234	3550	3250	900

